

LANYARD WITH ENERGY ABSORBERS

This single rope tether with energy absorber is attached to the safety harness at one end and to an anchor point at the other to protect the user in the event of a fall. The built-in energy absorber allows progressively retaining the user in the event of a fall. The two carabiners are built-in. The tether length cannot exceed 2.00 m.



- ▶ Tethers made of semistatic polyamide rope, 11 mm diameter, stretching <5%, quality resistance to traction forces
- ▶ Used when there is a fall hazard
- ▶ The built-in absorber dissipates energy during a fall thereby limiting the impact force felt by the user
- ▶ Buckle designed for hooking
- ▶ Connectors for the 54 mm diameter anchor point with automatic closing, maximum load 22kN
- ▶ Connectors for the 18 mm diameter harness with automatic closing, maximum load 22kN
- ▶ Available in 1.00 m and 1.75 m
- ▶ Maximum failure load: 2,200 kg

Product characteristics

Material	Polyamide
Maximum load (kg)	2200
Warranty (years)	5

To comply with the law and be sure to use equipment in perfect condition, all fall prevention PPE must be inspected every year and before use, always carry out a visual check. UNYCO personal protective equipment come with a 10-year guarantee from the date of manufacture and a 5-year guarantee from the date of initial use.

Ref.	Des.	Weight (kg)	CE	EAN barcode
09100401	Lanyard with energy absorbers 1.75M	1,140	CE	3178740209421
09100402	Lanyard with energy absorbers 1M	1,118	CE	3178740209438