

# SIMPLE ROPE LANYARD

A single worksite safety retaining tether made of semistatic rope, 11 mm diameter. This tether provides the link between the harness and the anchor point with no need for any additional component. The tether length cannot exceed 2.00 m.



- ▶ Tethers made of semistatic polyamide rope, 11 mm diameter
- ▶ Restrict the user's movements stopping them from approaching areas where there is a fall hazard
- ▶ This is a retaining mechanism not a fall prevention system
- ▶ Buckle designed for hooking
- ▶ Connectors for the 54 mm diameter anchor point with automatic closing, maximum load 22kN
- ▶ Connector for the 16 mm diameter harness with manual screw closing, maximum load 22kN
- ▶ Available in 1.00 m and 1.50 m
- ▶ Maximum failure load: 2,200 kg

## Product characteristics

<b>Material</b>	Polyamide
<b>Maximum load (kg)</b>	2200
<b>Warranty (years)</b>	5

To comply with the law and be sure to use equipment in perfect condition, all fall prevention PPE must be inspected every year and before use, always carry out a visual check. UNYCO personal protective equipment come with a 10-year guarantee from the date of manufacture and a 5-year guarantee from the date of initial use.

Ref.	Des.	Weight (kg)	CE	EAN barcode
09100421	Simple rope lanyard 1M	0,850	CE	3178740209469
09100422	Simple rope lanyard 1,50M	0,832	CE	3178740209476