

ELASTIC DOBLE LANYARD WITH ENERGY ABSORBERS

Ready for use, this double elastic fall prevention tether is fitted with an energy absorber that reduces the impact force after a fall from heights and two built-in connectors. It extends and retracts guaranteeing user comfort during their movements. The tether length cannot exceed 2.00 m. The double tether allows safely crossing a gap or moving from one anchor point to another without having to unhook.



- ▶ Retractable fall prevention tethers for easily moving around
- ▶ Retracted length 1.35 m and extended length 1.70 m (connectors included)
- ▶ Equipped with an energy absorber to reduce the impact force in the event of a fall
- ▶ Connectors for the 54 mm diameter anchor point with automatic closing, maximum load 22kN
- ▶ Connectors for the 18 mm diameter harness with automatic closing, maximum load 22kN
- ▶ Can be used on a thick structure
- ▶ 40 mm strap

Product characteristics

Material	Woven synthetic fiber
Warranty (years)	5

To comply with the law and be sure to use equipment in perfect condition, all fall prevention PPE must be inspected every year and before use, always carry out a visual check. UNYC® personal protective equipment come with a 10-year guarantee from the date of manufacture and a 5-year guarantee from the date of initial use.

Ref.	Des.	Weight (kg)	CE	EAN barcode
09100442	Elastic Y lanyard with energy absorbers 1,35M < 1,70M	1,860	CE	3178740209513