

DOBLE ROPE LANYARD

A double worksite safety retaining tether made of semistatic rope, 11 mm diameter. This tether provides the link between the harness and the anchor point with no need for any additional component. The tether length cannot exceed 2.00 m. The double tether allows safely crossing a gap or moving from one anchor point to another without having to unhook.



- ▶ Tethers made of semistatic polyamide rope, 11 mm diameter
- ▶ Restrict the user's movements stopping them from approaching areas where there is a fall hazard
- ▶ This is a retaining mechanism not a fall prevention system
- ▶ Buckle designed for hooking
- ▶ Connectors for the 54 mm diameter anchor point with automatic closing, maximum load 22kN
- ▶ Connector for the 18 mm diameter harness with automatic closing, maximum load 22kN
- ▶ Maximum failure load: 2.200 kg

Product characteristics

Material	Polyamide
Maximum load (kg)	2200
Warranty (years)	5

To comply with the law and be sure to use equipment in perfect condition, all fall prevention PPE must be inspected every year and before use, always carry out a visual check. UNYC® personal protective equipment come with a 10-year guarantee from the date of manufacture and a 5-year guarantee from the date of initial use.

Ref.	Des.	Weight (kg)	CE	EAN barcode
09100423	Doble rope lanyard 1.50M	1.604	CE	3178740209483